

**MILANO 1863** 

# A COMPUTATIONAL MODEL OF THE INTERACTION **BETWEEN CONTINUA AND NETWORKS:** POLITECNICO APPLICATION TO MICROCIRCULATION AND UREMY



The 33rd international CAE conference and exhibition

#### **POLITECNICO DI MILANO**



L. Possenti<sup>1</sup>, G. Casagrande<sup>1</sup>, S. Di Gregorio<sup>1</sup>, M.L. Costantino<sup>1</sup> and P. Zunino<sup>2</sup>


1 - Department of Chemistry, Materials and Chemical Engineering "Giulio Natta", Politecnico di Milano, Italy 2- MOX, Modelling and Scientific Computing, Department of Mathematics, Politecnico di Milano, Italy



### Introduction

The key role of microcirculation in haemodialysis is already known, since it is directly involved in the removal of toxins from the tissues. Recently, microcirculation alterations were pointed out in uremic patients.

We model the interaction of a network with the surrounding continua in order to describe the local phenomena involved in tissues and microcirculation vasculature in both healthy subjects and uremic patients.






Healthy subject

Patient on dialysis adapted from: Yeh et al. (2017)

# Model -

The finite element model - implemented using the open source software GetFEM++ (getfem.org) - has the unique ability of combining the following features:

- realistic vasculature
- coupled capillary and interstitial flow
- haematocrit dependent flow properties (Fåhræus-Lindqvist effect)
- prediction of red blood cells (RBCs) distribution along the vasculature (simulating plasma skimming effect)
- non-linear description of the lymphatic drainage.



Schematic view of a vessel network (Λ) and the surrounding tissue  $(\Omega)$ .

Ω: Porous media (Darcy's law)


A: Cylindrical conducts (Poiseuille's law)

Lymphatic drainage (non-linear function of fluid pressure)

Leakage across capillary wall (Starling's equation)

Parameters changed:

Case	Discharge haematocrit	Capillary hydraulic	Oncotic pressure	Capillary wall reflection	Capillary density
	(%)	conductivity (m <sup>2</sup> s kg <sup>-1</sup> )	gradient (mmHg)	coefficient (-)	S/V (m <sup>-1</sup> )
Healthy subject	45	1 x 10 <sup>-12</sup>	25	0,95	7000
Uremic patient	35	8.80 x 10 <sup>-12</sup>	19	0.75	4900



The model showed good agreement with the literature data available in terms of mean interstitial pressure (Ebah et al). After this preliminary comparison against experimental data, we analysed variations concerning the other variables using parameters referred to healthy subject and uremic patient. The model can be applied to deeper studies the alterations induced by uremy in the microcirculation.

# Reterences -

- Possenti, Casagrande, Costantino, Zunino; Int J Artif Organs; 40(8): 382 428, 2017
- → Di Gregorio; Master thesis, Politecnico di Milano, AY 2016/2017
- Yeh et al. Eur J Clin Invest; 47(9):630-637 2017

- ∨ Cattaneo, Zunino. IJNMBE, 30 (11), 1347-1371, 2014
- ∨ Cattaneo, Zunino. Networks and Heterogeneous Media, 9 (1), 135-159, 2014
- ≥ Ebah et al. Kidney International; 84: 980–988, 2013